#2804

ChemRisk/Shonka Research Associates, Inc., Document Request Form 5

(This section to be completed by subcontractor requesting document)
T. Lamb / 1034A Requestor Document Center (is requested to provide the following document)
Date of request 914195 Expected receipt of document 10/14/95
Date of request 9/14/95 Expected receipt of document 10/14/95 Document number KL550 pt 16 Date of document 10/26/59 Title and author (if document is pack 1
Title and author (if document is unnumbered)
(This section to be completed by Document Center)
Date request received 9-21-95
Date submitted to ADC\2-2\-95
Date submitted to HSA Coordinator 9-21-95
(This section to be completed by HSA Coordinator)
Date submitted to CICO 12-21-95 1-11-96
Date received from CICO 1-8-96 3/5/96
Date submitted to ChemRisk/Shonka and DOE3/5/91
This section to be completed by ChemRisk/Shonka Research Associates, Inc.)
Date document received
Signature

SANITIZED VERSION OF EXTRACT FROM ENGINEERING DEVELOPMENT DEPARTMENT WEEKLY ACTIVITIES REPORT WEEK ENDING OCTOBER 16, 1959

(EXTRACTED FROM CRD DOCUMENT # KL-550/PT16)

Compiled by
S. G. Thornton
Environmental Management Division
OAK RIDGE K-25 SITE
for the Health Studies Agreement

December 21, 1995

Oak Ridge K-25 Site
Oak Ridge, Tennessee 37831-7314
managed by
LOCKHEED MARTIN ENERGY SYSTEMS, INC.
for the U.S. DEPARTMENT OF ENERGY
under Contract DE-AC05-84OR21400

Py Kortman /sof 3/1/10

Report Number: KL-550, Part 16

This document consists of 11 pages,

No. 9 of 10 copies. Series A.

Date of Issue: October 26, 1959

RECEIVED

KL 550 PT16 9 A



DLU HISY 9 AN 9:17

ENGINEERING DEVELOPMENT DEPARTMENT Weekly Activities Report Week Ending October 16, 1959

Distribution

- 1. D. C. Brater
- 2. R. A. Carter
- H. L. Kaufman
- C. C. Littlefield
- 5. G. H. Montillon
- J. H. Pashley
- J. E. Rothfleisch
- 8. S. H. Smiley
- -9. P. R. Vanstrum ∠ 7029
- 10. M. E. Adams (RC)

ts cont

d prima Ay for s subject to relision are or correction. not represent a final report.

KL-550, Part 16 October 26, 1959 Page 11

Trace Elements in the Cascade

A recent change in cascade product withdrawal procedure has drastically reduced the amount of molybdenum and tungsten withdrawn at 306-7. Consequently, these impurities must either build up in the cascade or be forced out the top purge. In order to check the latter possibility, four successive gas samples were taken at 312-1, cell 2, during an interval in which the purge flow was an estimated 10% above normal. Only the analyses have been completed to date, and these indicate an average purge concentration of 11.6 ppm. or a feed to the alumina traps of 21.5 grams of uranium per day. The corresponding space recorder reading was 28 ppm. uranium. The reported uranium collection efficiency of the alumina traps*, 20%, together with the measured uranium values, suggests that further consideration be given the efficiencies of both the alumina traps and the hydrolysis recovery unit proposed for the 312 section**.

^{**} Pashley, J. H., Hydrolysis Recovery of Uranium from Purge Gases, Union Carbide Nuclear Company, Oak Ridge Gaseous Diffusion Plant, March 3, 1959 (KL-384).



^{*} Engineering Development Department Weekly Activities Report, Week Ending July 18, 1959, Union Carbide Nuclear Company, Oak Ridge Gaseous Diffusion Plant, July 18, 1959 (KL-12, Part 26).

DISTRIBUTION

- 1. K-25 Site Records (RC)
- 2. ChemRisk/Shonka Research Associates
- 3. S. G. Thornton (K-25 EMD)
- 4. DOE Public Reading Room